

HANDHELD SCANNERS

Product Group Guide



HANDHELD SCANNERS

Datalogic's Handheld Scanner product line offers products and solutions for automatic data capture and factory automation throughout the customer's entire value chain in the Retail, Manufacturing, Transportation & Logistics and Healthcare industries.

The wide range of general purpose hand held readers offer a variety of choices for most data collection activities. Product sets propose corded and cordless options together with best in class reading technologies, ready to solve current and future needs and applications.

Datalogic's PowerScan industrial handheld readers are data collection's definitive example of ruggedness and durability, coupled with outstanding performance and unyielding reliability.



HEALTHCARE



- Bedside Care
- Admittance
- Clinical Lab
- Surgical tool tracking
- Blood bank
- Pharmacies

MANUFACTURING



- Manufacturing Shop Floor
- Component Traceability
- Work-in-Progress
- Sub-Assembly
- Quality Control
- Time and Cost Analysis
- Control Machines Set-up
- In-line Inventory Control

TECHNOLOGIES

- Linear and area imaging technology for 1D and 2D bar codes
- Megapixel performance and distinctive white-illumination technology
- Bluetooth® and Datalogic's STAR Cordless System™ radio connectivity
- Datalogic's exclusive 3GL™ (3 Green Lights) and 'Green Spot' technology
- Great ergonomics and cutting edge design
- Rugged enclosures; Durable and reliable
- Healthcare models with Disinfectant-Ready enclosures and anti-microbial additives
- Wireless battery charging system
- Adjustable position cradle with scan-while-charging capability
- Smart battery management



RETAIL



- Point of Sale Checkout
- Shelf Replenishment
- Price Checking
- Store Inventory
- Goods Receiving
- Postal, Bank, Utilities,
- Public Administration
- Access Control, Entertainment

T&L



- Shipping / Receiving
- Parcel Preparation
- Picking / Put Away
- Automatic Sorting Back-Up
- End of Line Sorting

CORDLESS FEATURES

CONTACT	0 to 5 cm / 0 to 2 in
INSTINCTIVE	0 to 30 cm / 0 to 12 in
DISTANCE	0 to 100 cm / 0 to 39 in
LONG RANGE	0 to 250 cm / 0 to 98 in
AUTO RANGE	Up to 10 m / 3 ft

GENERAL

TD1100 FAMILY	HERON™ FAMILY		RIDA™ FAMILY
			
TD11XX	HD31XX	HD34XX	RIDA
The TD1100 series of linear imagers are a cost-effective solution for users who require close contact bar code reading. Used in Retail, Services, Banking, etc.	The Heron HD3100 is a linear imager bringing high style and modern technology to the point-of-sale. Available in a 'carbon-fiber' or 'silver' design.	The Heron HD3430 2D area imager brings elegance with advanced 2D reading technology to the modern point-of-sale. Available in a 'carbon-fiber' or 'silver' design.	The DBT6400 is a cordless area imager with Bluetooth® technology in a pocket-sized form factor. Available in a Standard or Healthcare model.

APPLICATIONS

Retail	X	X	X	X
Manufacturing		-	-	-
Transportation & Logistics	X	-	-	-
Healthcare	-	-	-	X

FEATURES

Reading Technology	Linear Imager	Linear Imager	Area Imager	Area Imager
Reading Range	Contact/Instinctive	Instinctive	Instinctive	Instinctive
Aiming System	Scan Line	Scan Line	4-Dot / Center Cross Aimer	4-Dot Aimer
Wide Scan Angle	-	X	-	-
Host Interface	RS-232 / USB / Keyboard Wedge / Wand Emulation	RS-232 / USB / Keyboard Wedge	RS-232 / USB / Keyboard Wedge	USB (with BC6020 only)

DATA CAPTURE

Bar Codes	1D	1D	1D and 2D	1D and 2D
Direct Part Marked (DPM) Codes	-	-	-	-
Digital Watermarks	-	-	-	-
Image Capture	-	-	X	X
Reads from Smartphone or screen displays	X	X	X	X
Datalogic's 'Green Spot' Technology	-	X	X	X

RUGGEDNESS / DURABILITY






IP Rating (Particulate and Liquid Sealing)	IP30	IP40	IP40	IP52
Drop to Concrete	1.5 m / 5.0 ft	1.5 m / 5.0 ft	1.5 m / 5.0 ft	1.5 m / 5.0 ft
Factory Warranty	5 Years	5 Years	5 Years	3 Years

CORDLESS FEATURES

Wireless Technology (STAR / Bluetooth)	-	-	-	Bluetooth® 4.0
Wireless Range - Travel Distance from Base	-	-	-	25.0 m / 82.0 ft
Display / Keypad for 2-Way Communication	-	-	-	
Batch Mode Capability	-	-	-	X
Battery Type	-	-	-	Li-Ion 700 mAh
Battery Life - Scans Between Charge	-	-	-	
Scan While Charging	-	-	-	

PURPOSE HANDHELD READERS

QUICKSCAN™ FAMILY

				
QW21XX	2131	QW24XX	2430	QD2500
The QuickScan Lite QW2100 linear imager is an entry level reader specifically for reading long and truncated bar codes which is common in some areas of the world.	The QuickScan 2131 series is a linear imager featuring an extra-wide field of view for reading long bar codes. Available in Desk, Bluetooth® and Mobile (STAR radio) versions.	The QuickScan Lite QW2400 2D corded area imager is designed for reading long and truncated 1D codes and larger 2D codes from close range. It has an extra-wide field of view which allows the capture of these bar codes.	The QuickScan 2430 series are 2D area imagers with a distinctive illumination and aiming system. Available in Desk, Bluetooth® and Mobile (STAR radio) versions.	The QuickScan QD2500 series are corded 2D area imagers providing best-in-class reading performance and snappiness, high reliability and full guidance with extreme precision aiming system.
X	X	X	X	X
X	X	X	-	X
X	-	X	X	X
-	-	-	-	X
Linear Imager	Linear Imager	Area Imager	Area Imager	Area Imager
Instinctive	Instinctive	Instinctive	Instinctive	Instinctive
Scan Line	Scan Line	Blue Aiming Dot	Two Blue Triangles	Two Blue-LED Triangles
X	X	X	-	-
RS-232 / USB / Keyboard Wedge	RS-232 / USB / Keyboard Wedge / OEM (IBM) USB	RS-232 / USB / Keyboard Wedge	RS-232 / USB / Keyboard Wedge / OEM (IBM) USB	RS232 / USB / USB-C / Keyboard Wedge
1D	1D	1D and 2D	1D and 2D	1D and 2D
-	-	-	-	-
-	-	-	-	X
-	-	-	-	X
X	X	X	X	X
X	X	X	X	X
IP42	IP42	IP42	IP42	IP52
1.5 m / 5.0 ft	1.5 m / 5.0 ft	1.5 m / 5.0 ft	1.5 m / 5.0 ft	1.5 m / 5.0 ft
3 Years	QD2131: 5 Years QBT2131: 3 Years QM2131: 3 Years	3 Years	QD2430: 5 Years QBT2430: 3 Years QM2430: 3 Years	5 Years
-	Bluetooth® 3.0 Class 2 STAR 2.0: 433 MHz	-	Bluetooth® 3.0 Class 2 STAR 2.0: 433 MHz	-
-	25.0 m / 82.0 ft	-	25.0 m / 82.0 ft	-
-	-	-	-	-
-	500 + Linear Codes	-	500 + Linear Codes	-
-	Li-Ion 1400 mAh	-	Li-Ion 1400 mAh	-
-	30,000 +	-	30,000 +	-
-	QBT2131, QM2131	-	QBT2430, QM2430	-

GENERAL PURPOSE HANDHELD READERS		WEARABLE SCANNERS
GRYPHON FAMILY		HANDSCANNER™
		
42XX	45XX	HANDSCANNER™
The Gryphon 42XX linear imagers provide the best-in-class reading performance on 1D bar codes coupled with disinfectant ready enclosures and a unique wireless battery charging system. Available in Desk, Bluetooth and Mobile (STAR radio) versions.	The Gryphon 45XX 2D area imagers provide a new cutting edge design, coupled with disinfectant ready enclosures, megapixel optics and a unique wireless battery charging system. Available in Desk, Bluetooth®, Mobile (STAR radio) and Healthcare versions.	The HandScanner is the lightest and smallest 2D wearable scanner in the market that allows workers to use both hands to pick faster and expand productivity while reducing repetitive useless motions and errors

APPLICATIONS

<i>Retail</i>	X	X	X
<i>Manufacturing</i>	X	X	X
<i>Transportation & Logistics</i>	X	X	X
<i>Healthcare</i>	X	X	X

FEATURES

<i>Reading Technology</i>	Linear Imager	Area Imager	Area Imager
<i>Reading Range</i>	Distance	Distance	Instinctive / Distance
<i>Aiming System</i>	Soft line viewfinder	4-Dot/Center Cross Aimer	Dot led or Cross laser
<i>Wide Scan Angle</i>	-	-	-
<i>Host Interface</i>	USB type C / USB / RS-232 / Keyboard Wedge / IBM46XX available with accessory cable	RS-232 / USB / Keyboard Wedge / IBM46XX available with accessory cable	Bluetooth HID, USB Serial Port

DATA CAPTURE

<i>Bar Codes</i>	1D	1D, 2D and Dotcode	1D and 2D
<i>Direct Part Marked (DPM) Codes</i>	-	-	X
<i>Digital Watermarks</i>	-	X	-
<i>Image Capture</i>	-	X	X
<i>Reads from Smartphone or screen displays</i>	X	X	X
<i>Datalogic's 'Green Spot' Technology</i>	X	X	-

RUGGEDNESS / DURABILITY

<i>IP Rating (Particulate and Liquid Sealing)</i>	IP52	xIP52	Water and dust resistant
<i>Drop to Concrete</i>	1.8 m / 5.9 ft	1.8 m / 5.9 ft	Multiple drops from 2m
<i>Factory Warranty</i>	GD4200: 5 Years GBT4200, GM4200: 3 Years	GD4500: 5 Years; GBT4500, GM4500: 3 Years	1 Year

CORDLESS FEATURES

<i>Wireless Technology (STAR / Bluetooth)</i>	Bluetooth® 4.0 STAR: 433 or 910 MHz	Bluetooth® 4.0 STAR: 433 or 910 MHz	Bluetooth Low Energy 4.0
<i>Wireless Range - Travel Distance from Base</i>	BT: Up to 100 m / 328 ft STAR: Up to 50 m / 164 ft	BT: Up to 100 m / 328 ft STAR: Up to 50 m / 164 ft	Using generic host device: Up to: 40 m (131 ft) Using HandScanner Gateway: Up to: 70 m (230 ft)
<i>Display / Keypad for 2-Way Communication</i>	-	-	-
<i>Batch Mode Capability</i>	X	X	-
<i>Battery Type</i>	Li-Ion 2550 mAh	Li-Ion 3250 mAh	Li-Ion 670 mAh
<i>Battery Life - Scans Between Charge</i>	GBT, GM: 80,000+	GBT: 80,000 + / GM: 60,000 +	10.000
<i>Scan While Charging</i>	GBT, GM with WLC4090 base station	GBT, GM with WLC4090 base station	-

INDUSTRIAL HANDHELD READERS

POWERSCAN™ FAMILY



91XX

The PowerScan 91XX linear imagers introduce a new green scanning line for outstanding 1D data collection. Available in Desk, Bluetooth® and Mobile (STAR radio) versions.

93XX

The PowerScan 93XX laser readers offer state-of-the-art performance in an industrial product. Available in Desk, Bluetooth® and Mobile (STAR radio) versions.

95XX

The PowerScan 95XX area imagers include omnidirectional reading with outstanding optical characteristics. Available in Desk, Bluetooth®, Mobile (STAR radio) and DPM versions.

95XX RETAIL

The durability of the PowerScan imagers are now available for the Retail sector. Available in Desk, Bluetooth® and Mobile (STAR radio) versions.

X	X	X	X
X	X	X	X
X	X	X	X
-	-	X	-

Linear Imager	Laser	Area Imager	Area Imager
Distance	Distance / Auto Range	Instinctive / Distance Auto Range DPM Models: Contact / Instinctive	Instinctive / Distance
Laser-like Line	Laser Line	Frame Aimer/Center Cross	4-Dot/Center Cross Aimer
-	-	X	-
RS-232 / USB / Keyboard Wedge / Ethernet / Industrial Fieldbus	RS-232 / USB / Keyboard Wedge / Ethernet / Industrial Fieldbus	RS-232 / USB / Keyboard Wedge / Ethernet / Industrial Fieldbus	RS-232 / USB / Keyboard Wedge

1D	1D	1D and 2D	1D and 2D
-	-	DPM Model	-
-	-	-	X
-	-	X	X
X	-	X	X
X	X	X	X

IP65	IP65	IP65	IP65
2.0 m / 6.6 ft	2.0 m / 6.6 ft	2.0 m / 6.6 ft	2.0 m / 6.6 ft
3 Years	3 Years	3 Years	3 Years

Bluetooth® 3.0 STAR: 433 or 910 MHz	Bluetooth® 3.0 STAR: 433 or 910 MHz	Bluetooth® 3.0 STAR 2.0: 433 or 910 MHz	Bluetooth® 3.0 STAR: 433 or 910 MHz
BT: Up to 100 m / 328 ft 433: Up to 100 m / 328 ft 910: Up to 400 m / 1,312 ft	BT: Up to 100 m / 328 ft 433: Up to 100 m / 328 ft 910: Up to 400 m / 1,312 ft	BT: Up to 90 m / 295 ft 433: Up to 120 m / 393 ft 910: Up to 220 m / 721 ft	BT: Up to 90 m / 295 ft 433: Up to 80 m / 262 ft 910: Up to 130 m / 426 ft
PM9100	PM9300	PM9500	PM9500 Retail
X	X	X	X
Li-Ion 3350 mAh	Li-Ion 3350 mAh	Li-Ion 3350 mAh	Li-Ion 3350 mAh
PBT: 80,000 + / PM: 60,000 +	PBT: 40,000 + / PM: 40,000 +	60,000 +	PBT: 60,000 + / PM: 60,000 +
-	-	-	Vertical Cradle



© 2021 Datalogic S.p.A. and/or its affiliates. • All rights reserved. Without limiting the rights under copyright, no part of this documentation may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means, or for any purpose, without the express written permission of Datalogic S.p.A. and/or its affiliates. • Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S. and the E.U. • PowerScan, QuickScan, Gryphon and Heron are trademarks of Datalogic S.p.A. and/or its affiliates, registered in many countries, including the U.S. and the E.U. • RIDA and Datalogic STAR Cordless System are trademarks of Datalogic S.r.l. and/or its affiliates. • The Bluetooth word mark and logos are trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Datalogic Group companies is under license. • All other trademarks and brands are property of their respective owners. • Product specifications are subject to change without notice. • PG-HH-EN Revision E 20210316

www.datalogic.com